

United Nuclear

SCIENTIFIC EQUIPMENT & SUPPLIES

BISMUTH

SAFETY DATA SHEET

DATE OF LAST REVISION: 04/30/15

Section 1: Identification

Product Name: Bismuth

CAS Number: 7440-69-9 / **EC Number:** 231-177-4

Company: United Nuclear Scientific
125 N. 8th Street
Klamath Falls, OR 97601
Tel: 541-205-6855

24 HR. EMERGENCY Telephone Number

VelocityEHS (USA): 800-255-3924

Section 2: HAZARD IDENTIFICATION

Signal Word: Warning



Hazard Statements:

H228: Flammable solid

Precautionary Statements:

P210: Keep away from heat/sparks/flames. No smoking
P280: Wear protective gloves/protective clothing/eye protection/face protection
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/light equipment.
P370 + P378: In case of fire: Use CO₂ powder for extinction.

HMIS Health Ratings (0-4):

	Powder	Pieces & Larger
Health:	1	1
Flammability:	2	0
Physical:	1	0

BISMUTH
SAFETY DATA SHEET

Section 3: Composition/Information on Ingredients

Chemical characterization: Metal

CAS# Description: 7440-69-9

Percentage: 100 wt%

EC number: 231-177-4

Section 4: FIRST AID MEASURES

General Treatment: Seek medical attention if symptoms persist.

Special Treatment: None

Important Symptoms: None

Eye Contact: Flush eyes with water, blinking often for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

Skin Contact: Wash affected area with mild soap and water. Remove any contaminated clothing.

Inhalation: Remove to fresh air. If required, give artificial respiration. Seek medical advice.

Ingestion: Give one to two glasses of water and induce vomiting. Never induce vomiting or give anything by mouth to an unconscious person.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing Media: Do not use water for metal fires. Use special powder, sand, CO₂

Flammability: Non-flammable, except as powder.

Special Fire Fighting Procedure: Use full-face, self contained breathing apparatus with full protective clothing to prevent contact with skin and eyes.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate respiratory and protective equipment specified in special protection information. Isolate spill area and provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for disposal. Take care not to raise dust.

Environmental Precautions: Isolate runoff to prevent environmental pollution.

Section 7: HANDLING AND STORAGE

Handling Precautions for safe handling: Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities Store in a cool dry place in a tightly sealed container.

Work/Hygienic Maintenance: Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air.

Ventilation: Provide sufficient ventilation to maintain concentration at or below threshold limit.

BISMUTH
SAFETY DATA SHEET

Section 8: EXPOSURE CONTROL/PERSONAL PROTECTION

Permissible Exposure Limits:	None
Threshold Limit Value:	None
Special Equipment:	None
Respiratory Protection:	Dust respirator
Protective Gloves:	Rubber gloves
Eye Protection:	Safety glasses or goggles
Body Protection:	Protective work clothing. Wear close-toed shoes and long sleeves/pants.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form:	Powder, Granules, Pellets, Sputtering target, Custom parts
Color:	Metallic Grey
Odor:	Odorless
Water Solubility:	Insoluble
Boiling Point:	1564° C
Melting Point:	271°C
Flash Point:	N/A
Autoignition Temperature:	N/A
Density:	9.78 g/cc
Molecular Weight:	208.980 g/mol

Section 10: STABILITY AND REACTIVITY

Reactivity:	Oxidizing agents, Acids
Chemical Stability:	Stable under recommended storage conditions
Incompatible Conditions:	None
Hazardous Decomposition Products:	Metal oxide fume

Section 11: TOXICOLOGICAL INFORMATION

Potential Health Effects:

Eyes: May cause irritation

Skin: May cause irritation

Ingestion: May cause irritation

Inhalation: May cause irritation

BISMUTH
SAFETY DATA SHEET

Chronic: Bismuth and bismuth compounds are often poorly absorbed. Should absorption occur, however, exposure may cause loss of appetite, headache, skin rash, exodermatitis, kidney injury and jaundice. Repeated or prolonged exposure may cause a bismuth line or black spots on the gums, foul breath and salivation. Exposure to bismuth may cause injury to the mouth, esophagus and stomach. Symptoms may include loss of appetite, headache, skin rash, kidney damage and jaundice.

Signs & Symptoms: N/A
Aggravated Medical Conditions: N/A
Median Lethal Dose: 5000 mg/kg for rat by mouth
Carcinogen: N/A

Section 12: ECOLOGICAL INFORMATION

Aquatic Toxicity: Low

Persistent Bioaccumulation Toxicity: No

Very Persistent, Very Bioaccumulative: No

Notes: N/A

Section 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, national, and international regulations

Section 14: TRANSPORT INFORMATION

Hazardous: Hazardous as powder only



Hazard Class: 4.1 Flammable solids
Packing Group: III
UN Number: UN3089
Proper Shipping Name: Metal powders, flammable, n.o.s. (Bismuth)

BISMUTH
SAFETY DATA SHEET

Section 15: REGULATORY INFORMATION

Sec 302 Extremely Hazardous: No
Sec 304 Reportable Quantities: N/A
Sec 313 Toxic Chemicals: No

Section 16: OTHER INFORMATION

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.